

SIENNA® RFGS

Wireless gateway incl. wireless remote for all SIENNA® actuators

SIENNA® RFGS is a gateway for mapping wireless channels to SIENNA® powerline devices.

- Plug-in module with RF-Receiver and **SIENNA®** Powerline output.
- Compatible with all Easywave RF-transmitters e.g. remote control or door-/window contacts.
- 32 configurable RF-Channels.
- Configurable with a screwdriver.
- Includes a 5-Channel remote control for usage with all **SIENNA®** actuators.



Technical Data (Gateway):

Frequency	868,30 MHz
Modulation	FSK
Range (RF)	Outdoors: ca. 100 m; indoors: ca. 30 m
RF-Protocol	Easywave; compatible with all Easywave remote controls (http://www.eldat.de)
Channel Assignment	Maximum 32 RF-Channels
Power Supply	230V~/50 Hz, power consumption max. 1.5W
Standby Power Consumption	< 0.2W
Operating Temperature	-25° C to +70° C
Safety Compliance	EN 300 220-1 V1.3.1 (2000-09), EN 300 220-3 V1.1.1 (2000-09), EN 500 65-1

Technical Data (Remote):

Wireless Properties	See Gateway
RF-Channels	5 RF-Channels, with On / Up und Off / Down button
Power Supply	1 x 3V-Battery, CR2032
Operating Temperature	-25° C to +70° C
Safety Compliance	EN 300 220-1 V1.3.1 (2000-09), EN 300 220-3 V1.1.1 (2000-09), EN 500 65-1

Product name: RFGS-ST01-H01
EAN number: 4260194736017